

AD-A161 457

LIMITING PERFORMANCE OF NONLINEAR SYSTEMS WITH
APPLICATIONS TO HELICOPTER (U) VIRGINIA UNIV
CHARLOTTESVILLE DEPT OF MECHANICAL AND AEROSPACE

1/1

UNCLASSIFIED

W D PILKEY AUG 85 ARO-18643 10-EG


F/G 20/11

NL

END

END

END



MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS-1963-A

2

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER ARO 18643.10-EG	2. GOVT ACCESSION NO. N/A	3. RECIPIENT'S CATALOG NUMBER N/A
4. TITLE (and Subtitle) Limiting Performance of Nonlinear Systems with Applications to Helicopter Vibration Control		5. TYPE OF REPORT & PERIOD COVERED 1 Aug 82 - 31 Oct 84 Final
		6. PERFORMING ORG. REPORT NUMBER UVA/5-MAE86/101
7. AUTHOR(s) W. D. Pilkey		8. CONTRACT OR GRANT NUMBER(s) DAAG 29-82-K-0164
PERFORMING ORGANIZATION NAME AND ADDRESS Division of Applied Mechanics Department of Mechanical & Aerospace Engineering University of Virginia, Charlottesville, VA.		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
CONTROLLING OFFICE NAME AND ADDRESS U. S. Army Research Office Post Office Box 12211 Research Triangle Park, NC 27709		12. REPORT DATE August 1985
MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 6
		15. SECURITY CLASS. (of this report) Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE N/A

DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited.

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

NA

DTIC
ELECTE
NOV 22 1985
S
A
E
D

18. SUPPLEMENTARY NOTES

The view, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

vibration control	reanalysis
helicopter	limiting performance
two-beam helicopter model	

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

Several problems concerning the vibration control of helicopters were studied. Methodology for introducing structural modifications leading to vibration reduction has been developed. In particular, a formulation for attaching appendages to continuous structural members was completed and applied to a two-beam helicopter model.

AD-A161 457

DTIC FILE COPY

Limiting Performance of Nonlinear Systems with Applications to Helicopter Vibration Control

FINAL REPORT

W.D. Pilkey

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Distribution _____	
Availability _____	
Dist _____	
A-1	

August 1985



U. S. Army Research Office

Grant Number: DAAG 29-82-K-0164

University of Virginia

APPROVED FOR PUBLIC RELEASE:
DISTRIBUTION UNLIMITED.

I. STATEMENT OF PROBLEM STUDIED

Several problems concerning the vibration control of helicopters were studied. Methodology for introducing structural modifications leading to vibration reduction has been developed. In particular, a formulation for attaching appendages to continuous structural members was completed and applied to a two-beam helicopter model. A procedure for the optimal placement and subsequent tuning of vibration suspension devices has been devised. The placement and tuning is based on the existence of "fixed" points in the displacement-frequency response curves. The distance of these fixed points from the resonant frequencies to be controlled are an indication of the goodness of placement. Furthermore, a new theory for spreading two natural frequencies of a helicopter model was developed.

II. SUMMARY OF THE MOST IMPORTANT RESULTS

1. Eigenvalue Reanalysis of Locally Modified Structures Using Generalized Rayleigh's Method

Approximate eigenvalue reanalysis methods for locally modified structures have been developed based on the generalized Rayleigh's quotients. For simple modifications such as adding springs, masses, or changing truss member cross-sectional areas, closed form formulas have been derived. The methods have been applied to several examples with good results.

2. Generalized Dunkerley's Estimates for Eigenvalues for Conservative Linear Systems

A. Lower Bound Estimates for Higher Modes

Based on the relationship between the eigenvalues of a linear conservative system and the coefficients of the characteristic polynomial, lower bounds for eigenvalues are computed. The bound on the first eigenvalue is the classical Dunkerley bound. This is a lower bound. The estimated bounds for higher modes do not enjoy this guarantee. Test cases show that we can get the lower bound for up to the third mode. Danilevsky's method was used to generate the characteristic polynomial.

B. Improved Estimates of Fundamental Modes

In the literature it has been shown that improved lower bounds can be obtained by taking traces of matrices that are powers of the dynamical matrix. This is numerically inefficient since it involves multiplications of matrices. Based on the Newton's identity, the traces of powers of the dynamical matrix can be computed recursively from the coefficients of the characteristic equations. No matrix multiplication is involved. From these traces, upper bound estimates can also be computed.

3. Reshaping the Frequency Spectrum of a Structure

Some of the significant results of this period deal with the reshaping of the spectrum of structures by the selective modification of element properties. The problem is that of shifting natural frequencies away from a particular level, such as that of a driving force frequency. In particular, the goal is to spread two frequencies, i.e., decrease one frequency and simultaneously increase the other frequency, by structural modifications. Normally this involves a two step process,

whereby each frequency is shifted separately to achieve the desired changes. However, a new method has been formulated which will (1) identify the best structural elements for modification in order to spread two frequencies and (2) find the optimum magnitude of the modifications to the element stiffness matrices to effect the desired changes. The formulation is based on the use of a 2nd order expansion of the frequencies with respect to the changes in element stiffnesses. The first order terms are used in the identification of appropriate elements to be modified and the full second order expansion is used to optimize the amount of change. A 108 element helicopter (tail boom) model was used to demonstrate the success of the method in spreading two frequencies.

4. Modal Formulation for the Limiting Performance of a Helicopter Mode

The limiting performance problem has been formulated in terms of the modal characteristics of a helicopter. The mode shapes can be obtained experimentally or can be generated computationally.

III. JOURNAL PUBLICATIONS

1. "Generalized Dunkerley Bounds for Discrete Systems," L. Kitis, B. P. Wang, and W. D. Pilkey, J. of Engineering Mechanics, Vol. 110, No. 6 (1984), pp. 1011-1014.
2. "Synthesis of Dynamic Vibration Absorbers," B.P. Wang, L. Kitis, W. D. Pilkey, A. Palazzolo, Journal of Vibration, Acoustics, Stress, and Reliabilty in Design, Vol. 107, (1985), pp. 161-166.
3. "Stuctural Modifications to Achieve Antiresonance in Helicopters," B. P. Wang, L. Kitis, W. D. Pilkey, and A. Palazzolo, Journal of Aircraft, Vol. 19, No.6 (1982), pp. 499-504.
4. "Helicopter Vibration Reduction by Local Structural Modification," B. P. Wang, L. Kitis, W. D. Pilkey, and A. Palazzolo, Journal of the American Helicopter Society, Vol. 27, No. 3 (1982), pp. 43-47.
5. "Eigenvalue Reanalysis of Locally Modified Structures Using a Generalized Rayleigh's Method," B. P. Wang and W.D. Pilkey, AIAA Journal, (1985).
6. "Transient Response Optimization of Vibrating Structures by Liapunov's Second Method," B. P. Wang, L. Kitis, W. D. Pilkey, Journal of Sound and Vibration, Vol. 96, No. 4 (1984).
7. "Optimal Frequency Response Shaping by Appendant Structures," L. Kitis, W. D. Pilkey, B. P. Wang, Journal of Sound and Vibration, Vol. 95, No. 2 (1984), pp. 161-175.
8. "Vibration Reduction Over a Frequency Range," L. Kitis, W. D. Pilkey, B. P. Wang, Journal of Sound and Vibration, Vol. 89, No. 4 (1983), pp. 559-569.
9. "Reanalysis of Continuous Dynamic Systems with Continuous Modifications," Y. Okada, B. P. Wang, W. D. Pilkey, Shock and Vibration Bulletin, Vol. 54, No. 3, (1984), pp. 35-42.

10. "A Computational Technique for Optimizing Correction Weights and Axial Location of Balance Planes of Rotating Shafts," W. D. Pilkey, J. Bailey, and J. D. Smith, Journal of Vibrations, Acoustics, Stress, and Reliability in Design, Vol. 105 (1983), pp. 90-93.
11. "Discrete Modifications to Continuous Dynamic Systems," Y. Okada, B. P. Wang, W. D. Pilkey, Shock and Vibration Bulletin, Vol. 54, No. 3, (1984), pp. 29-34.
12. "Optimal Frequency Response Modification by Added Passive Structures," L. Kitis, W. D. Pilkey, B. P. Wang, Journal of Aircraft, Vol. 20, No. 11 (1983), pp. 897-898.

IV. PARTICIPATING SCIENTIFIC PERSONNEL

PILKEY, W. D., Principle Investigator

KITIS, L., Received Ph.D.

MAYER, G., Ph.D. Candidate. Will receive degree soon.

WANG, B. P., Associate Research Professor

END

FILMED

1-86

DTIC